

Safety Data Sheet

Printing date 01/05/2017

Revised On 01/05/2017

1 Identification of the substance and manufacturer

Trade name: ASPHALT BLACK STRIPE
Product code: 0000200663
Product category: PC9a Paints and coatings.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification**Classification of the substance or mixture**

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Skin Irrit. 2 H315 Causes skin irritation.
 STOT SE 3 H335 May cause respiratory irritation.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word**Hazard statements**

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes skin irritation.

Precautionary statements

May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.
 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER/doctor if you feel unwell.
 If skin irritation occurs: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 Protect from sunlight. Store in a well-ventilated place.
 Store in a well-ventilated place. Keep container tightly closed.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients**Chemical characterization: Mixtures**

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

1317-65-3	Calcium Carbonate	21.62%
74-98-6	propane	17.64%
64742-89-8	VM&P Naphtha	16.26%
106-97-8	n-butane	10.36%
142-82-5	heptane	8.06%
64742-47-8	Mineral Spirits	5.76%
67-63-0	Isopropyl Alcohol	2.25%
1330-20-7	xylene (mix)	1.99%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/05/2017

Revised On 01/05/2017

Trade name: ASPHALT BLACK STRIPE

(Contd. of page 1)

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures**Personal precautions, protective equipment and emergency procedures:**Wear protective equipment. Keep unprotected persons away.
Use respiratory protective device against the effects of fumes/dust/aerosol.**Methods and material for containment and cleaning up:**

Ensure adequate ventilation.

7 Handling and storage**Precautions for safe handling
Storage requirements:**Use only in well ventilated areas.
Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.**8 Exposure controls/personal protection****Components with limit values that require monitoring at the workplace:****74-98-6 propane**

PEL (United States GHS)	Long-term value: 1800 mg/m ³ , 1000 ppm
REL (United States GHS)	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV (United States GHS)	refer to Appendix F in TLVs&BEIs book; NIC-EX

106-97-8 n-butane

REL (United States GHS)	Long-term value: 1900 mg/m ³ , 800 ppm
TLV (United States GHS)	Short-term value: (2370) mg/m ³ , (1000) ppm NIC-EX

142-82-5 heptane

PEL (United States GHS)	Long-term value: 2000 mg/m ³ , 500 ppm
REL (United States GHS)	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
TLV (United States GHS)	Short-term value: 2050 mg/m ³ , 500 ppm Long-term value: 1640 mg/m ³ , 400 ppm

67-63-0 Isopropyl Alcohol

PEL (United States GHS)	Long-term value: 980 mg/m ³ , 400 ppm
REL (United States GHS)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (United States GHS)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI

1330-20-7 xylene (mix)

PEL (United States GHS)	Long-term value: 435 mg/m ³ , 100 ppm
REL (United States GHS)	Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV (United States GHS)	Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI

Ingredients with biological limit values:**67-63-0 Isopropyl Alcohol**

BEI (United States GHS)	40 mg/L Medium: urine Time: end of shift at end of workweek Parameter: Acetone (background, nonspecific)
-------------------------	---

1330-20-7 xylene (mix)

BEI (United States GHS)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-------------------------	--

Hygienic protection:Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Do not eat or drink while working.**Breathing equipment:**A respirator is generally not necessary when using this product outdoors or in large open areas.
In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.**Hand protection:**

Nitrile gloves.

Eye protection:Protective gloves. The glove material must be impermeable and resistant to the substance.
Tightly sealed goggles**9 Physical and chemical properties****Appearance:**

Aerosol.

Odor:

Aromatic

(Contd. on page 3)

Safety Data Sheet

Printing date 01/05/2017

Revised On 01/05/2017

Trade name: ASPHALT BLACK STRIPE

(Contd. of page 2)

Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range	Undetermined.
Boiling point:	-44 °C (-47 °F)
Flash point:	-19 °C (-2 °F)
Flammability (solid, gas):	Extremely flammable.
Decomposition temperature:	Not determined.
Auto igniting:	Product is not self-igniting.
Danger of explosion:	In use, may form flammable/explosive vapour-air mixture.
Lower Explosion Limit:	1.5 Vol %
Upper Explosion Limit:	10.9 Vol %
Vapor pressure:	Not determined.
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)
Vapor density	Not determined.
Evaporation rate	Not applicable.
Partition coefficient: n-octonal/water:	Not determined.
Solubility:	Not determined.
Viscosity:	Not determined.
VOC content (less exempt solvents):	62.8 %
MIR Value:	0.59
Solids content:	24.4 %

10 Stability and reactivity

Reactivity:	Stable at normal temperatures.
Conditions to avoid:	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability:	Not fully evaluated.
Possibility of hazardous reactions:	No dangerous reactions known.
Incompatible materials:	No further relevant information available.
Hazardous decomposition:	No dangerous decomposition products known.

11 Toxicological information**LD/LC50 values that are relevant for classification:****106-97-8 n-butane**

Inhalative LC50/4 h 658 mg/l (rat)

67-63-0 Isopropyl Alcohol

Oral	LD50	4570 mg/kg (rat)
Dermal	LD50	13400 mg/kg (rab)
Inhalative	LC50/4 h	30 mg/l (rat)

1330-20-7 xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

Carcinogenic categories**IARC (International Agency for Research on Cancer)**

67-63-0	Isopropyl Alcohol	3
1330-20-7	xylene (mix)	3

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Ecotoxicological effects:
Remark: Toxic for fish
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.

(Contd. on page 4)

Safety Data Sheet

Printing date 01/05/2017

Revised On 01/05/2017

Trade name: ASPHALT BLACK STRIPE

(Contd. of page 3)

14 Transport information

UN-Number	UN1950
DOT	N/A
DOT	UN1950
ADR	Consumer Commodity ORM-D
Transport hazard class(es):	Aerosols, flammable
Class	1950 Aerosols
Marine pollutant:	2.1
Special marking (ADR):	No
Special precautions for user:	Symbol (fish and tree)
EMS Number:	Warning: Gases
Packaging Group:	F-D,S-U
UN "Model Regulation":	--
	UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

67-63-0 Isopropyl Alcohol

1330-20-7 xylene (mix)

TSCA: All ingredients are listed.**CPSC:** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

1333-86-4 Carbon black

100-41-4 ethyl benzene

CANADIAN ENVIRONMENTAL PROTECTION ACT:**WHMIS Symbols for Canada:**All hazardous ingredients for this product appear on the Canadian Domestic Substance List.
A - Compressed gas**EPA:**

142-82-5 heptane

1330-20-7 xylene (mix)

D

I

16 Other information

Contact:	Regulatory Affairs
Date of preparation / last revision	01/05/2017 / -